



FWT-CT



WRC-HPC

- › Wide operating range
- › Easy installation and maintenance
- › 3-speed fan motor
- › Double-intake centrifugal fans
- › Excellent air flow and air distribution
- › Flexibility via interchangeable water connection side
- › High power air flow
- › Insulated with self-extinguishing class 1 heat insulation
- › Removable washable air filter (self-extinguishing class 1)
- › **Wireless remote control up to 9m distance, availability of a wired or simplified controller**
- › LED indicator gives an indication on the (normal or wrong) operation of the unit



Heating only & Cooling only

Indoor unit				02	03	04	05	06
Cooling capacity	Total capacity	High	kW	2.43	2.70	3.31	4.54	5.28
	Sensible capacity	High	kW	1.85	2.02	2.64	3.43	4.10
Heating capacity	2-Pipe	High	kW	3.22	3.52	4.40	6.01	5.26
Power input	High		W	31	32	42	53	72
Current input	High		A	0.19	0.20	0.21	0.29	0.34
	Medium		A	0.18	0.20	0.20	0.26	0.32
	Low		A	0.17	0.19	0.19	0.25	0.31
Dimensions	Unit	HeightxWidthxDepth	mm	288x800x206	288x800x206	288x800x206	310x1,065x224	310x1,065x224
Weight	Unit		kg	9	9	9	14	14
	Operation weight		kg	9.5	9.6	9.6	15	15
Heat exchanger	Water volume		l	0.52	0.58	0.58	0.95	0.95
Water flow	Cooling		l/h	420	460	570	780	910
	Heating		l/h	420	460	570	780	910
Water pressure drop	Cooling		kPa	34	24	31	28	32
	Heating		kPa	29	20	25	25	29
Fan	Type			Cross flow fan	Cross flow fan	Cross flow fan	Cross flow fan	Cross flow fan
	Air flow rate	High	m³/h	442	476	629	866	1,053
Sound power level	High		dBA	45	48	55	55	59
Sound pressure level	High		dBA	34	35	42	42	46
Piping connections	Drain	OD	mm	19	19	19	19	19
Water connections	Std. heat exchanger		inch	1/2	1/2	1/2	1/2	1/2